

<p>c) wheel spray protection</p> <p><b>Note:</b> Body overhang is the distance from the vertical centre line of the tire to the end of the body.</p> <p>Underbody height is the distance from the highest point of the bottom of the body overhang behind the rear wheel to the ground.</p>	<p>c) - missing fender, mudflap or mudguard if vehicle's body overhang measurement is three times or less the underbody height measurement</p> <p>- fenders, mudflap or mudguard not full tread width of tire, fender contacts tire, or coverage of the tire tread circumference is not, at a minimum, 15° to the front and 90° to the rear of the vertical centre line of the wheel measured at the centre of the wheel rotation</p>	
---	---	--

ITEM AND METHOD OF INSPECTION	REJECT IF	
	GENERAL CONDITIONS	HAZARDOUS CONDITIONS
	<ul style="list-style-type: none"> <li>- distance between the bottom of the mudflap or mudguard to the ground exceeds 210 mm, or the top of the mudflap or mudguard does not reach up to the top of the tire or a body element (whichever is lowest)</li> <li>- fender, mudflap or mudguard has a tear or wear hole that is larger than 100 mm across the longest dimension, or the aggregated longest dimensions of multiple holes in a single fender, mudflap or mudguard exceeds 100 mm</li> </ul>	